

PLUMBING DRAWING / REVISION LOG				
SHEET NUMBER	SHEET TITLE	DATE	ISSUE	
			ISSUE	DATE
P0.01	PLUMBING COVER SHEET	02/27/2024	DESIGN DEVELOPMENT	03/18/2024
P1.01	PLUMBING 1ST AND 2ND FLOOR PLANS	02/27/2024	50% CD	03/18/2024
P1.02	PLUMBING 3RD FLOOR AND ROOF PLANS	02/27/2024	PERMIT SET	03/25/2024
P3.01	PLUMBING SCHEDULES			
P4.01	PLUMBING DETAILS			
P5.01	PLUMBING RISER DIAGRAMS			
P5.02	PLUMBING RISER DIAGRAMS			
P6.01	PLUMBING UNIT PLANS			
P6.02	PLUMBING UNIT PLANS			
P6.03	PLUMBING UNIT PLANS			
P6.04	PLUMBING UNIT PLANS			

PIPING SYMBOLS	
SYMBOL	DESCRIPTION
---	COLD WATER PIPING
---	HOT WATER PIPING
---	NATURAL GAS PIPING
---	SANITARY, SOIL, WASTE PIPING
---	SANITARY ABOVE GROUND PIPING
ST	STORM PIPING
V	VENT PIPING
PD	PUMP DISCHARGE
C	CONDENSATE PIPING

KEY TO SYMBOLS	
SYMBOL	DESCRIPTION
ACU 1-1	EQUIPMENT IDENTITY (SEE EQUIPMENT ABBREVIATION LIST AND SCHEDULES)
1-1	EQUIPMENT DESIGNATION
1-1	SYSTEM NUMBER (IF APPLICABLE)
R 1	RISER TYPE. REFER TO ABBREVIATIONS
R 1	RISER DESIGNATION
R 1	RISER NUMBER. REFER TO PLANS AND/OR RISER DIAGRAMS
1-1	SECTION NUMBER
1-1	SECTION DESIGNATION
1-1	SECTION DRAWING NUMBER
△	REVISION NUMBER
①	SHEET NOTE NUMBER
●	CONNECT NEW TO EXISTING

KEY TO SYMBOLS	
SYMBOL	DESCRIPTION
—	PIPE UP
—	PIPE DOWN
⊘	SHUT OFF VALVE
⊘	THREE WAY VALVE
⊘	GAS COCK
⊘	WATER METER
⊘	REDUCED PRESSURE ZONE ASSEMBLY
⊘	CHECK VALVE
⊘	PRESSURE REDUCING VALVE
⊘	PRESSURE RELIEF VALVE
⊘	BALANCING VALVE
⊘	STRAINER
+	UNION
—	CAPPED LINE
⊘	THERMOMETER
⊘	THERMOSTATIC MIXING VALVE
⊘	FLOOR DRAIN
⊘	FLOOR CLEAN OUT
⊘	CLEAN OUT
⊘	POINT OF CONNECTION
⊘	ROOF DRAIN W/ OVERFLOW
⊘	HOSE BIB
⊘	PUMP
⊘	VACUUM BREAKER

ABBREVIATIONS	
ABV	ABOVE
AD	ACCESS DOOR
AFF	ABOVE FINISHED FLOOR
BFP	BACK FLOW PREVENTOR
BLDG	BUILDING
BLW	BELOW
BSMT	BASEMENT
BTU	BRITISH THERMAL UNIT
CB	CATCH BASIN
CFH	CUBIC FEET PER HOUR
CFM	CAST IRON
C	CENTER LINE
CLG	CEILING
CMU	CONCRETE MASONRY UNIT
CO	CLEAN OUT
COL	COLUMN
CONC	CONCRETE
CONN	CONNECTION
CSST	CORRUGATED STAINLESS STEEL TUBING
CW	COLD WATER
CG	DEGRESS CENTIGRADE
DFU	DRAINAGE FIXTURE UNIT
DIA	DIAMETER
DIAG	DIAGRAM
DISCH	DISCHARGE
DN	DOWN
DWG	DRAWING
(E)	EXISTING
EA	EACH
EHD	EQUIVALENT HYDRAULIC DIAMETER
EL	ELEVATION
ENT	ENTERING
EQ	EQUAL
EQUIP	EQUIPMENT
EQUIV	EQUIVALENT
EW	ELECTRIC WATER COOLER
EW	EYE WASH
EXT	EXTERNAL
F	DEGREES FAHRENHEIT
FAI	FRESH AIR INLET
FCO	FLOOR CLEAN OUT
FD	FLOOR DRAIN
FL	FLANGE
FLEX	FLEXIBLE
FLR	FLOOR
FP	FIRE PROTECTION
FPM	FEET PER MINUTE
FPS	FEET PER SECOND
FT	FEET
G	GAS
GA	GAUGE
GALV	GALVANIZED
GCO	GRADE CLEAN OUT
GC	GENERAL CONTRACTOR
GPD	GALLONS PER DAY
GPH	GALLONS PER HOUR
GPM	GALLONS PER MINUTE
GW	GREASE WASTE
HB	HOSE BIBB
HD	HEAD
HR	HOUR
HTR	HEATER
HW	HOT WATER
HWR	HOT WATER RETURN
ID	INTERNAL DIAMETER
INCL	INCLUDING
INV	INVERT
LAV	LAVATORY
MAX	MAXIMUM
MBH	1000 BRITISH THERMAL UNITS
MC	MECHANICAL CONTRACTOR
MFR	MANUFACTURER
MIN	MINIMUM
MISC	MISCELLANEOUS
MTD	MOUNTED
(N)	NEW
NC	NORMALLY CLOSED
NIC	NOT IN CONTRACT
NH	NO HUB
No	NUMBER
NO	NORMALLY OPEN
NPW	NON-POTABLE WATER
NOM	NOMINAL
NTS	NOT TO SCALE
OP	OPENING
OZ	OUNCE
PART	PARTIAL
PERF	PERFORATED
PEX	CROSS LINKED POLYETHYLENE TUBING
PH	PHASE
PIV	POST INDICATOR VALVE
POS	POSITIVE
PRESS	PRESSURE
PS	PRESSURE SWITCH
PRV	PRESSURE REDUCING VALVE
PSI	POUNDS PER SQUARE INCH
PSIG	POUNDS PER SQUARE INCH GAUGE
PSIA	POUNDS PER SQUARE INCH ABSOLUTE
PV	PLUG VALVE
PVC	POLYVINYL CHLORIDE
PC	PLUMBING CONTRACTOR
QTY	QUANTITY
RD	ROOF DRAIN
REDD	REQUIRED
RM	ROOM
RPZ	REDUCED PRESSURE ZONE BACKFLOW PREVENTER
RTU	ROOF TOP UNIT
S	SOIL
SAN	SANITARY
SCH	SCHEDULE
SHO	SHOWER
SPEC	SPECIFICATION
SQFT	SQUARE FEET
S/S	SERVICE SINK
STD	STANDARD
SUP	SUPPLY
SYS	SYSTEM
TDH	TOTAL DYNAMIC HEAD
TEMP	TEMPERATURE
TS	TEMPER SWITCH
TYP	TYPICAL
URN	URNAL
V	VENT
VTR	VENT THRU ROOF
W	WASTE
WC	WATER CLOSET
WM	WATER METER
WSFU	WATER SUPPLY FIXTURE UNIT

MATERIAL SCHEDULE													
SYSTEMS	PIPE				FITTINGS				JOINTS				
	REQUIRED	NO-HUB C.I. PIPE	P.V.C. SCH. 40 DRAINAGE PIPE	C.P.V.C. SCH. 40	BLACK IRON	GALVANIZED STEEL	COPPER TUBING TYPE 'L'	COPPER TUBING TYPE DWV	DUCTILE IRON PIPE	FLANGED POLYETHYLENE	FLANGED POLYETHYLENE	FLANGED POLYETHYLENE	FLANGED POLYETHYLENE
SANITARY BUILDING DRAIN (UNDER GROUND)	●	●	●	●	●	●	●	●	●	●	●	●	●
SANITARY BUILDING DRAIN	●	●	●	●	●	●	●	●	●	●	●	●	●
SANITARY STACKS	●	●	●	●	●	●	●	●	●	●	●	●	●
SANITARY BRANCHES	●	●	●	●	●	●	●	●	●	●	●	●	●
VENT STACKS	●	●	●	●	●	●	●	●	●	●	●	●	●
VENT BRANCHES	●	●	●	●	●	●	●	●	●	●	●	●	●
STORM BUILDING DRAIN (UNDER GROUND)	●	●	●	●	●	●	●	●	●	●	●	●	●
STORM BUILDING DRAIN	●	●	●	●	●	●	●	●	●	●	●	●	●
STORM STACKS	●	●	●	●	●	●	●	●	●	●	●	●	●
STORM BRANCHES	●	●	●	●	●	●	●	●	●	●	●	●	●
C.W. (SERVICE)	●	●	●	●	●	●	●	●	●	●	●	●	●
C.W. (DISTRIBUTION)	●	●	●	●	●	●	●	●	●	●	●	●	●
H.W. (DISTRIBUTION)	●	●	●	●	●	●	●	●	●	●	●	●	●
GAS (DISTRIBUTION)	●	●	●	●	●	●	●	●	●	●	●	●	●
C.W. (UNITS)	●	●	●	●	●	●	●	●	●	●	●	●	●
H.W. (UNITS)	●	●	●	●	●	●	●	●	●	●	●	●	●
GAS (UNITS)	●	●	●	●	●	●	●	●	●	●	●	●	●
FLUE POWER VENTING	●	●	●	●	●	●	●	●	●	●	●	●	●
INDIRECT WASTE	●	●	●	●	●	●	●	●	●	●	●	●	●
SUMP DISCHARGE	●	●	●	●	●	●	●	●	●	●	●	●	●
ELEVATOR SHAFT SUMP PUMP DISCHARGE	●	●	●	●	●	●	●	●	●	●	●	●	●

NOTES:  
1. PROVIDE DUCT ALTERNATE PRICE TO INSTALL ALTERNATE MATERIAL.  
ALL MATERIALS INSTALLED WITHIN A PLENUM ARE TO HAVE A 25 PLUME SPREAD & 50 SMOKE DEVELOPED WHEN TESTED ACCORDING TO ASTM E84 OR BE INSULATED WITH 3M FIRE BARRIER PLENUM WRAP 5A+, OR APPROVED EQUAL, SO AS TO COMPLY WITH THE ABOVE REQUIREMENTS.

PLUMBING FIXTURE SCHEDULE (TBD)									
TAG	DESCRIPTION	MAKE	MODEL	FAUCET	PIPING CONNECTIONS				COMMENTS
					COLD	HOT	TRAP	VENT	
KS-1	UNDERMOUNT SINGLE BOWL SS KITCHEN SINK	LEGACY	LS-78		1/2"	1/2"	1 1/2"	1 1/2"	
LAV-1	CULTURED MARBLE TOPS LAVATORY			PROFLO	3/8"	3/8"	1 1/2"	1 1/2"	
WC-1	ADA COMPLIANT CADET PRO RIGHT HEIGHT ELONGATED 215AB.104.020 WHITE FINISH	AMERICAN STANDARD	215AB.104.020		1/2"	NA	INTEGRAL	2"	
BT-1	BATH TUB	STERLING	71041111-DW	PROFLO	1/2"	1/2"	1 1/2"	1 1/2"	
SH-1	60"x34" SHOWER PAN	STERLING	72131100-0	PROFLO	1/2"	1/2"	2"	1 1/2"	
HB-1	WALL FAUCET WITH BACKFLOW PREVENTER	ZURN	Z1341-BFP		1/2"	NA	NA	NA	
HB-2	ANIT-SIPHON, AUTOMATIC DRAINING NON FREEZE WALL HYDRANT WITH INTEGRAL BACKFLOW PREVENTER	ZURN	Z1321-C		1/2"	NA	NA	NA	
REF-1	ICE MAKER OUTLET BOX FOR REFRIGERATOR OR COFFEE MAKER, WITH 1/2 TURN HAMMER BALL VALVE OUTLET	OATEY	39125	INCLUDED	3/8"	NA	NA	NA	

NOTES:  
1. CONTRACTOR TO COORDINATE ALL PLUMBING FIXTURES OF UNITS AND AMENITY SPACES WITH ID/ARCH DRAWING.

ELECTRIC HOT WATER HEATERS													
TAG	CAPACITY (GAL.)	1ST HR RATING	RECOVERY RISE (OPH)	ELEMENT POWER (KW)	ENERGY FACTOR (%)	POWER REQ. (V/PH)	AMP (FLA)	MOCF (FLA)	DIAMETER (IN.)	HEIGHT (IN.)	WATER CONN. (IN.)	MANUFACTURER MAKE AND MODEL	COMMENTS
EWH-1	47	63	21	6	92	240/1	25	-	20	60 1/16	3/4	BRADFORDWHITE RE35016	NOTES 1

NOTES:  
1. PROVIDE ALL PIPING ACCESSORIES AND APPURTENANCES AS PER THE HOT WATER HEATER INSTALLATION DETAIL.



FLOOR DRAIN SCHEDULE							
TAG	LOCATION	MAKE	MODEL	DESCRIPTION	OUTLET SIZE	TRAP SEAL	TRAP PRIMER
FD-1	BATHROOMS	ZURN	FD-2240-PV2	PVC WOOD DECK DRAIN	2"	4"	NO
FD-2	MECHANICAL ROOMS (TBD)	ZURN	Z507-P	7" MEDIUM DUTY C.I. DRAIN	3"	4"	NO

NOTES:  
1. ALL TRAPPED FLOOR DRAINS SHALL BE INSTALLED WITH AN ASSE 1072 TRAP SEAL PROTECTION DEVICE.


BACKFLOW PREVENTERS / VACUUM BREAKERS SCHEDULE			
APPLICATION	MFR.	MODEL #	DISCRPTION
DISHWASHER	WATTS	188A	ANIT-SIPHON VACUUM BREAKER
SERVICE SINK (TBD)	WATTS	8	HOSE CONNECTION VACUUM BREAKER
WATER HEATER	WATTS	LF7	DUAL CHECK
BUILDING WATER SERVICE	WATT	LF009	REDUCED PRESSURE ZONE ASSEMBLY

NOTES:  
1. ADDITIONAL BACKFLOW PREVENTER OR VACUUM BREAKERS ARE NOT REQUIRED WHERE SUCH DEVICES ARE INSTALLED INTEGRAL TO THE EQUIPMENT.






**PLUMBING UNDER SLAB PLAN**  
SCALE: 1/8" = 1'-0"



**PLUMBING FIRST FLOOR PLAN**  
SCALE: 1/8" = 1'-0"



**PLUMBING SECOND FLOOR PLAN**  
SCALE: 1/8" = 1'-0"

GAS METERS MUST BE 2 FT CLEAR FROM OPERABLE WINDOWS. NO CLEARANCE IS REQUIRED IF WINDOWS ARE FIXED.  
PROVIDE NEW GAS SERVICE STANDARD PRESSURE OF 7 INCH. OF W.C. COORDINATE WITH UTILITY PROVIDER  
10 UNIT METERS GAS METERS 3 STACK HIGH

WATER SERVICE FROM DEVELOPMENT, SEE CIVIL FOR CONTINUATION (TYP.)  
1" METER IN PIT SEE CIVIL (TYP.)

4" FIRE SERVICE IN HEATED CLOSET WITH SLIDING DOOR OR 2 DOOR OPTION AT FRONT SIDE FOR MAINTENANCE ACCESS, WATTS 3500CDA  
4" DCDA WITH AIR GAP DISCHARGE OUTSIDE SPLASH BOX OR DISCHARGE INDIRECT WASTE TO FLOOR DRAIN

ARMEN KHACHATURIAN  
PRINCIPAL IN CHARGE  
CM, JP, SM  
PROJECT TEAM  
AK  
CREATED BY  
BRIEF DESCRIPTION  
**PLUMBING 1ST AND 2ND FLOOR PLANS**

RELEASED FOR	DATE
<input type="checkbox"/> SCHEMATIC DESIGN	1/26/2024
<input type="checkbox"/> DESIGN DEVELOPMENT	2/21/2024
<input type="checkbox"/> 50% CDS	3/18/2024
<input type="checkbox"/> PERMIT	3/25/2024

REVISIONS

NO.	DESCRIPTION

















1 1/2" = 1'-0"  
 1" = 1'-0"  
 1/2" = 1'-0"  
 1/4" = 1'-0"



**WATER SUPPLY RISERS** 1  
 NTS



**GAS SUPPLY RISERS** 1  
 NTS


PROVIDE NEW GAS SERVICE STANDARD  
 PRESSURE OF  
 7 INCH. OF W.C., COORDINATE WITH UTILITY  
 PROVIDER  
 10 GAS METERS  
 GAS METERS 3 STACK HIGH

**PLUMBING RISERS**  
**DIAGRAM**



RELEASED FOR	DATE
<input type="checkbox"/> SCHEMATIC DESIGN	1/26/2024
<input type="checkbox"/> DESIGN DEVELOPMENT	2/21/2024
<input type="checkbox"/> 50% CDS	3/18/2024
<input checked="" type="checkbox"/> PERMIT	3/25/2024

REVISIONS

NO.	DESCRIPTION



**TYPICAL SANITARY RISERS 1**  
NTS




- GENERAL NOTES:**
1. THE TOTAL OF DFU FOR THE STACKS DIFFERS FROM THAT OF THE HORIZONTAL PIPING DUE TO BATHROOM GROUPS BEING SPLIT UP ONTO SEPARATE STACKS.
  2. STACK VENTS CAN BE COMBINED AS NECESSARY TO MINIMIZE ROOFTOP PENETRATIONS

**GENERAL NOTE**

1. DRAINAGE FIXTURE UNIT COUNTS ARE BASED ON NATIONAL STANDARD PLUMBING CODE 2021 TABLE 11.4.1&11.4.4A.
2. BUILDING DRAINS AND SEWER IS BASED ON NATIONAL STANDARD PLUMBING CODE 2021 TABLE 11.5.1A&11.5.1B.

**NOTE**

1. THESE PLUMBING RISER DRAWINGS AND PIPING LAYOUT ARE DIAGRAMMATIC.
2. DO NOT SCALE THESE PLUMBING DRAWINGS.
3. PROVIDE PLUMBING SHOP DRAWINGS FOR APPROVAL.
4. CONTRACTOR SHALL COORDINATE OFFSET OF PIPING AS SHOWN ON RISERS AND FLOOR PLANS.



**PLUMBING RISERS**  
**DIAGRAM**

RELEASED FOR	DATE
<input type="checkbox"/> SCHEMATIC DESIGN	1/26/2024
<input type="checkbox"/> DESIGN DEVELOPMENT	2/21/2024
<input type="checkbox"/> 50% CDS	3/18/2024
<input checked="" type="checkbox"/> PERMIT	3/25/2024




REVISIONS

NO.	DESCRIPTION







RELEASED FOR	DATE
<input type="checkbox"/> SCHEMATIC DESIGN	1/26/2024
<input type="checkbox"/> DESIGN DEVELOPMENT	2/21/2024
<input type="checkbox"/> 50% CDS	3/18/2024
<input checked="" type="checkbox"/> PERMIT	3/25/2024

REVISIONS

1/2" = 1'-0"  
1/4" = 1'-0"  
1/8" = 1'-0"










**PLUMBING UNIT PLANS**

RELEASED FOR	DATE
<input type="checkbox"/> SCHEMATIC DESIGN	1/26/2024
<input type="checkbox"/> DESIGN DEVELOPMENT	2/21/2024
<input type="checkbox"/> 50% CDS	3/18/2024
<input checked="" type="checkbox"/> PERMIT	3/25/2024







REVISIONS



RELEASED FOR	DATE
<input type="checkbox"/> SCHEMATIC DESIGN	1/26/2024
<input type="checkbox"/> DESIGN DEVELOPMENT	2/21/2024
<input type="checkbox"/> 50% CDS	3/18/2024
<input checked="" type="checkbox"/> PERMIT	3/25/2024








REVISIONS



RELEASED FOR	DATE
<input type="checkbox"/> SCHEMATIC DESIGN	1/26/2024
<input type="checkbox"/> DESIGN DEVELOPMENT	2/21/2024
<input type="checkbox"/> 50% CDS	3/18/2024
<input checked="" type="checkbox"/> PERMIT	3/25/2024

REVISIONS



RELEASED FOR	DATE
<input type="checkbox"/> SCHEMATIC DESIGN	1/26/2024
<input type="checkbox"/> DESIGN DEVELOPMENT	2/21/2024
<input type="checkbox"/> 50% CDS	3/18/2024
<input checked="" type="checkbox"/> PERMIT	3/25/2024

DESIGN CRITERIA

- SPRINKLER SYSTEM LAYOUT AND CALCULATIONS SHALL COMPLY WITH 2021 BUILDING CODE OF NEW JERSEY, FIRE CODE OF NEW JERSEY, NFPA 13 (2019), OWNER'S INSURANCE COMPANY REQUIREMENTS AND GOOD ENGINEERING PRACTICE.
- THE SPRINKLER SYSTEM SHALL BE HYDRAULICALLY CALCULATED BASED ON COORDINATED SHOP DRAWINGS.
- SPACE OCCUPANCY CLASSIFICATION: AS PER NFPA STANDARD IS: LIGHT HAZARD IN RESIDENTIAL AREAS, EXTRA HAZARD GROUP II IN CAR STACKERS PARKING AREAS, ORDINARY HAZARD GROUP I IN MECHANICAL ROOMS & PARKING SPACE, ORDINARY HAZARD GROUP II IN COMMERCIAL RETAIL SPACES.
- SPRINKLERS PROTECTION SHALL PROVIDE A MINIMUM DENSITY OF DISCHARGE OF 0.1 GPM / SQ.FT. IN LIGHT HAZARD AREAS; 0.15 GPM / SQ.FT. IN OHI AREAS AND 0.2 GPM / SQ.FT. IN OH2 AREAS. DESIGN AREA FOR WET SYSTEMS IS 1500 SQ.FT.; DESIGN AREA FOR DRY SYSTEM IS 1950 SQ.FT.
- SPRINKLER COVERAGE IS 225 SQ.FT. FOR LIGHT HAZARD AREAS AND 130 SQ.FT. FOR ORDINARY HAZARD LOCATIONS.
- RESIDENTIAL SPRINKLER HEADS ARE PERMITTED TO PROTECT THE DWELLING UNITS. REQUIRED DENSITY SHALL BE 0.10 GPM/SQ.FT. IN THE DWELLING UNITS. RESIDENTIAL SPRINKLER COVERAGE SHALL BE AS PER THE MANUFACTURER'S TABLES.
- MINIMUM PRESSURE AT ANY SPRINKLER HEAD SHALL BE 7.0 PSI OR THE MANUFACTURER'S RECOMMENDED PRESSURE WHICHEVER IS THE HIGHER.

PROVIDE SIDEWALL SPRINKLERS ON 3RD FLOOR UNITS FED FROM THE FLOOR BELOW

CONTRACTOR TO PROVIDE EXPANSION FITTINGS FOR AREAS WITH EXPANSION JOINTS

PERFORMANCE SPECIFICATION CRITERIA

SPRINKLER PLANS AS SHOWN ARE FOR BIDDING PURPOSES ONLY. SPRINKLER CONTRACTOR IS TO OBTAIN CURRENT HYDRANT FLOW TEST DATA AND PROVIDE HYDRAULIC CALCULATIONS FOR SYSTEM PIPE SIZING IN ACCORDANCE WITH NFPA 13R. CONTRACTOR IS TO SUBMIT SHOP DRAWINGS INDICATING HYDRAULIC CALCULATIONS, PIPING LAYOUT & SIZING. SHOP DRAWINGS AND CALCULATIONS ARE TO BE SIGNED & SEALED BY A PROFESSIONAL ENGINEER, AND REVIEWED AND APPROVED BY THE AUTHORITY HAVING JURISDICTION. ALL WORK IS TO BE DONE IN ACCORDANCE WITH NFPA 13R, INTERNATIONAL BUILDING CODE 2021 AND ALL OTHER STATE, LOCAL, GOVERNING AND APPLICABLE CODES.

ABBREVIATIONS

ABV	ABOVE
ABD	AUTOMATIC BALL DRIP
AD	ACCESS DOOR
AFF	ABOVE FINISHED FLOOR
BFP	BACK FLOW PREVENTER
BLDG	BLDG
BLW	BELOW
BSMT	BASEMENT
CI	CAST IRON
C	CENTER LINE
CEL	CEILING
CO	CLEAN OUT
COL	COLUMN
CONC	CONCRETE
CONN	CONNECTION
CV	CHECK VALVE
°C	DEGREES CENTIGRADE
DIA	DIAMETER
DIAG	DIAGRAM
DISCH	DISCHARGE
DN	DOWN
DWG	DRAWING
(E)	EXISTING
EA	EACH
ELEV	ELEVATION
ENT	ENTERING
EQ	EQUIVALENT
EQUIP	EQUIPMENT
EQUIV	EQUIVALENT
EXT	EXTERNAL
°F	DEGREES FAHRENHEIT
FAI	FRESH AIR INLET
FD	FLOOR DRAIN
FH	FIRE HYDRANT
FHC	FIRE HOSE CABINET
FHR	FIRE HOSE RACK
FL	FLANGE
FLX	FLEXIBLE
FLR	FLOOR
FP	FIRE PROTECTION
FFM	FEET PER MINUTE
FFS	FEET PER SECOND
FT	FEET
GALV	GALVANIZED
GC	GENERAL CONTRACTOR
GPD	GALLONS PER DAY
GPH	GALLONS PER HOUR
GPM	GALLONS PER MINUTE
GV	GATE VALVE
HC	HUNG CEILING
HD	HOUR
HR	HEATER
HR	INTERNAL DIAMETER
ID	INCLUDING
JP	JOCKEY PUMP
MAX	MAXIMUM
MFR	MANUFACTURER
MIN	MINIMUM
MISC	MISCELLANEOUS
MTD	MOUNTED
(N)	NEW
NC	NORMALLY CLOSED
NIC	NOT IN CONTRACT
No	NUMBER
NO	NORMALLY OPEN
NPW	NON-POTABLE WATER
NOM	NOMINAL
NTS	NOT TO SCALE
OPC	OPENING
OS&Y	OUTSIDE SCREW & YOKE
OZ	OUNCE
PART	PARTIAL
PERF	PERFORATED
PEX	CROSS LINKED POLYETHYLENE TUBING
PH	PHASE
PV	POST INDICATOR VALVE
PO	PLUGGED OUTLET
POS	POSITIVE
PRESS	PRESSURE
PS	PRESSURE SWITCH
PSI	POUNDS PER SQUARE INCH
PSIG	POUNDS PER SQUARE INCH GAUGE
PSIA	POUNDS PER SQUARE INCH ABSOLUTE
PV	PLUG VALVE
QTY	QUANTITY
RCV	RISER CONTROL VALVE
REQD	REQUIRED
ROOM	ROOM
RPZ	REDUCED PRESSURE ZONE BACKFLOW PREVENTER
SCH	SCHEDULE
SCV	SPRINKLER CONTROL VALVE
SPEC	SPECIFICATION
STD	STANDARD
SUP	SUPPLY
SYST	SYSTEM
TDH	TOTAL DYNAMIC HEAD
TEMP	TEMPERATURE
TS	TAMPER SWITCH
TYP	TYPICAL
UG	UNDERGROUND
V	VENT
VO	VALVED OUTLET
W	WASTE
WF	WATER FLOW SWITCH
WM	WATER METER

NOTE : SYMBOL LIST AND ABBREVIATIONS PROVIDED FOR CONVENIENCE ONLY. NOT EVERY SYMBOL OR ABBREVIATION IS NECESSARY USED IN.

SYMBOLS

— F —	FIRE MAIN
— SP —	SPRINKLER MAIN
— DR —	DRAIN PIPE
— FSP —	COMBINED FIRE STANDPIPE SPRINKLER
— DSP —	DRY STANDPIPE
— WSP —	WET STANDPIPE
●	BALL VALVE
○	HOSE VALVE
⊕	FLOOR CONTROL VALVE ASSEMBLY
⊖	CHECK VALVE
⊕ ⊖	CONTROL VALVE (OS & Y)
⊕ ⊖ ⊕	PRESSURE REDUCING VALVE
⊕ ⊖ ⊕ ⊖	ALARM CHECK VALVE ASSEMBLY
⊕ ⊖ ⊕ ⊖ ⊕	DRY PIPE VALVE ASSEMBLY
⊕ ⊖ ⊕ ⊖ ⊕ ⊖	OUTSIDE WALL HYDRANT
⊕ ⊖ ⊕ ⊖ ⊕ ⊖ ⊕	OUTSIDE GROUND HYDRANT
⊕ ⊖ ⊕ ⊖ ⊕ ⊖ ⊕ ⊖	NON FREEZE WALL HYDRANT
⊕ ⊖ ⊕ ⊖ ⊕ ⊖ ⊕ ⊖ ⊕	HOSE BIBB
⊕ ⊖ ⊕ ⊖ ⊕ ⊖ ⊕ ⊖ ⊕ ⊕	FIRE DEPARTMENT CONNECTION (SIAMESE)
⊕ ⊖ ⊕ ⊖ ⊕ ⊖ ⊕ ⊖ ⊕ ⊕ ⊕	FIRE DEPARTMENT TEST HEADER
⊕ ⊖ ⊕ ⊖ ⊕ ⊖ ⊕ ⊖ ⊕ ⊕ ⊕ ⊕	FIRE HYDRANT
⊕ ⊖ ⊕ ⊖ ⊕ ⊖ ⊕ ⊖ ⊕ ⊕ ⊕ ⊕ ⊕	FIRE HOSE VALVE
⊕ ⊖ ⊕ ⊖ ⊕ ⊖ ⊕ ⊖ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕	ALARM GONG
⊕ ⊖ ⊕ ⊖ ⊕ ⊖ ⊕ ⊖ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕	POST INDICATOR VALVE
⊕ ⊖ ⊕ ⊖ ⊕ ⊖ ⊕ ⊖ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕	FIRE DEPARTMENT VALVE
⊕ ⊖ ⊕ ⊖ ⊕ ⊖ ⊕ ⊖ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕	PRE-ACTION VALVE
⊕ ⊖ ⊕ ⊖ ⊕ ⊖ ⊕ ⊖ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕	OPENING THROUGH STEEL
⊕ ⊖ ⊕ ⊖ ⊕ ⊖ ⊕ ⊖ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕	TERMINATION POINT OF DEMOLITION AND CAP
⊕ ⊖ ⊕ ⊖ ⊕ ⊖ ⊕ ⊖ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕	CONNECT NEW TO EXISTING
⊕ ⊖ ⊕ ⊖ ⊕ ⊖ ⊕ ⊖ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕	HYDRAULIC CALCULATION POINT INDICATOR
⊕ ⊖ ⊕ ⊖ ⊕ ⊖ ⊕ ⊖ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕	FIRE HOSE RACK/CABINET
⊕ ⊖ ⊕ ⊖ ⊕ ⊖ ⊕ ⊖ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕	FIRE HOSE VALVE PUMPS: 1. HOUSE PUMP (AKA FILL PUMP) 2. FIRE PUMP (SHOW GPM & MANUAL OR AUTOMATIC) 3. BOOSTER PUMP (SHOW GPM)
⊕ ⊖ ⊕ ⊖ ⊕ ⊖ ⊕ ⊖ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕	TAMPER SWITCH
⊕ ⊖ ⊕ ⊖ ⊕ ⊖ ⊕ ⊖ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕	WATER FLOW SWITCH
⊕ ⊖ ⊕ ⊖ ⊕ ⊖ ⊕ ⊖ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕	EXISTING SPRINKLER PIPING TO REMAIN
⊕ ⊖ ⊕ ⊖ ⊕ ⊖ ⊕ ⊖ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕ ⊕	NEW SPRINKLER PIPING
⊕ ⊖ ⊕ ⊖ ⊕ ⊖ ⊕ ⊖ ⊕	EXISTING SPRINKLER PIPING TO BE REMOVED
⊕ ⊖ ⊕ ⊖ ⊕ ⊖ ⊕ ⊖ ⊕	DETAIL REFERENCE: DETAIL NUMBER
⊕ ⊖ ⊕ ⊖ ⊕ ⊖ ⊕ ⊖ ⊕	DETAIL REFERENCE: DRAWING NUMBER
⊕ ⊖ ⊕ ⊖ ⊕ ⊖ ⊕ ⊖ ⊕	RISER CALLOUT: RISER TYPE
⊕ ⊖ ⊕ ⊖ ⊕ ⊖ ⊕ ⊖ ⊕	RISER CALLOUT: RISER NUMBER
⊕ ⊖ ⊕ ⊖ ⊕ ⊖ ⊕ ⊖ ⊕	RISER CONTROL VALVE

FIRE PROTECTION MATERIAL SCHEDULE

SYSTEM	PIPE	FITTINGS	JOINTS	REMARKS
BURIED BUILDING FIRE SERVICE	PVC	PVC	PVC	3" AND LARGER PIPING
BURIED BUILDING FIRE SERVICE	PVC	PVC	PVC	2" PIPING
SPRINKLER	CPVC	CPVC	SOCKET	BLAZEMASTER CPVC PIPE MAY BE USED IN RESIDENTIAL APPLICATIONS ONLY WHEN INSTALLED AS PER MANUFACTURER'S SPECIFICATIONS.
DRAIN PIPE	STEEL SCHED 40 GALVANIZED	GALVANIZED	THREADED	

NOTES:  
1. ALL MATERIALS SELECTED ON THIS SCHEDULE MUST BE APPROVED BY THE LOCAL AUTHORITIES.

CODE COMPLIANCE

2021 INTERNATIONAL BUILDING CODE  
(WITH NEW JERSEY ADOPTED AMENDMENTS)  
2021 INTERNATIONAL FIRE CODE WITH AMENDMENTS  
NFPA 13 – 2019  
NFPA 14 – 2019  
NFPA 20 – 2019

SCHEDULE OF SPRINKLER HEADS

SYMBOL	MFR.	MODEL	SIN	TYPE	LOCATION	FINISH & REMARKS	TEMP. RATING	'K' FACTOR	HEAD COVERAGE	MIN. FLOW	MIN. PRESS.	LISTINGS
⊙	VIKING	RESIDENTIAL	VK474	RESIDENTIAL CONCEALED PENDENT	THROUGHOUT THE FACILITY IN RESIDENTIAL AREAS WITH SUSPENDED CEILINGS UNLESS OTHERWISE NOTED	AS SELECTED BY ARCHITECT	155°F	5.8	20'x20'	AS LISTED	AS LISTED	
○	RELIABLE	GS-56	RA3415	QUICK RESPONSE CONCEALED PENDENT SPRINKLER	THROUGHOUT THE FACILITY IN CORRIDORS AND UTILITY CLOSET AREAS	AS SELECTED BY ARCHITECT	155°F	5.6	AS LISTED	AS LISTED	AS LISTED	
▶	VICTAULIC	FIRELOCK	V4431	QUICK RESPONSE RECESSED HORIZONTAL SIDEWALL	THROUGHOUT THE FACILITY ON 3RD FLOOR RESIDENTIAL UNITS OR WITHIN RESIDENTIAL AREA	AS SELECTED BY ARCHITECT	155°F	4.4	AS LISTED	AS LISTED	AS LISTED	
▷	VIKING	VK157	VK157	DRY VERTICAL SIDEWALL SPRINKLERS	THROUGHOUT THE FACILITY UNDER GARAGE DOORS	AS SELECTED BY ARCHITECT	155°F	5.6	AS LISTED	AS LISTED	AS LISTED	


- NOTES:
- SPRINKLER HEADS SHALL BE INSTALLED AS PER MANUFACTURER'S REQUIREMENT.
  - PROVIDE METAL WIRE GUARDS WHERE SPRINKLERS ARE SUBJECT TO DAMAGE AND SPRINKLER HEADS LOCATED UNDER HVAC DUCTS IN FIRE PROTECTION EQUIPMENT ROOMS WHEN LOCATED LOWER THAN 7'-0" A.F.F. ETC.
  - ALL SPRINKLER HEADS THROUGHOUT THE FACILITY SHALL BE OF THE ORDINARY TEMPERATURE RATING EXCEPT AS FOLLOWS:
    - SPRINKLER HEADS IN FIRE PROTECTION ROOMS SHALL BE OF INTERMEDIATE TEMPERATURE RATING (200').
    - SPRINKLER HEADS LOCATED CLOSE TO HEATERS, SHALL BE OF THE TEMPERATURE RATING AS REQUIRED BY NFPA 13R.
  - ALL HEAT GENERATING EQUIPMENT WHICH CAN AFFECT THE TEMPERATURE RATING OF THE SPRINKLER HEADS SHALL BE CLEARLY IDENTIFIED ON THE SHOP DRAWINGS PRIOR TO SUBMISSION FOR APPROVAL.
    - SPRINKLER HEADS MINIMUM FLOW & MINIMUM PRESSURE REQUIREMENTS TO BE BASED ON HYDRAULIC CALCULATION DESIGN DENSITIES.
    - ALL SPRINKLER HEAD FINISHES TO BE APPROVED BY ARCHITECT.
    - SPRINKLERS FOR THE ATTIC TO BE LISTED AS AN ATTIC SPRINKLER (VIKING MODEL V-66)

FIRE PROTECTION DRAWING / REVISION LOG

ISSUE	DATE	ISSUE	DATE	ISSUE	DATE
● NEW OR REVISED ISSUE		○ NON REVISED ISSUE			
	02/21/2024		03/18/2024		03/25/2024
	DESIGN DEVELOPMENT		50% CD		PERMIT SET


SHEET NUMBER	SHEET TITLE	ISSUE	DATE	ISSUE	DATE	ISSUE	DATE
FP0.01	FIRE PROTECTION COVER SHEET	●		○			
FP1.01	FIRE PROTECTION 1ST AND 2ND FLOOR PLANS	●		○			
FP1.02	FIRE PROTECTION 3RD FLOOR AND ROOF PLANS	●		○			
FP3.01	FIRE PROTECTION SCHEDULES	●		○			
FP4.01	FIRE PROTECTION DETAILS	●		○			
FP6.01	FIRE PROTECTION UNIT PLANS	●		○			
FP6.02	FIRE PROTECTION UNIT PLANS	●		○			
FP6.03	FIRE PROTECTION UNIT PLANS	●		○			
FP6.04	FIRE PROTECTION UNIT PLANS	●		○			













**FIRE PROTECTION GENERAL NOTES:**

- SPRINKLER DESIGN IN ACCORDANCE WITH NFPA 13R
- LIGHT HAZARD OCCUPANCY IN ALL UNITS, 20'x20' RESIDENTIAL SPRINKLER
- SPRINKLER CONTRACTOR TO VERIFY CEILING HEIGHTS/SOFFITS, ANY OPEN TO ABOVE/BELOW SPACES, AND FOLLOW OBSTRUCTION RULES IN ACCORDANCE WITH NFPA 13R.
- PROVIDE DRY SIDEWALL HEADS FOR CLOSETS IN GARAGE OR SPACES SUBJECT TO FREEZING
- SPRINKLER HEADS TO MEET MANUFACTURERS MINIMUM PRESSURE AND FLOW REQUIREMENTS (TYPICAL FOR ALL UNITS)

IF INSULATION CANNOT BE INSTALLED ON TOP OF SPRINKLER PIPES ON THE THIRD FLOOR, PROVIDE SIDEWALL SPRINKLERS ON 3RD FLOOR UNITS FED FROM THE FLOOR BELOW



**FIRE PROTECTION THIRD FLOOR PLAN**  
SCALE: 1/8" = 1'-0"



**FIRE PROTECTION ROOF PLAN**  
SCALE: 1/8" = 1'-0"

RELEASED FOR	DATE
<input type="checkbox"/> SCHEMATIC DESIGN	1/26/2024
<input type="checkbox"/> DESIGN DEVELOPMENT	2/21/2024
<input type="checkbox"/> 50% CD'S	3/18/2024
<input checked="" type="checkbox"/> PERMIT	3/25/2024

REVISIONS


NO.	DESCRIPTION









1 1/2" = 1'-0"  
 1" = 1'-0"  
 1/2" = 1'-0"  
 1/4" = 1'-0"



1 TYPICAL HORIZONTAL SIDEWALL SPRINKLER HEAD DETAIL  
 NOT TO SCALE




2 TYPICAL SPRINKLER ARM OVER DETAIL  
 NOT TO SCALE




NOTES:  
 1. CLEVIS HANGERS REQUIRED ON PIPING LARGER THAN 1"  
 2. GENERAL PURPOSE HANGERS MAY BE USED ON 1" SPRINKLER PIPING ONLY.

3 TYPICAL HANGER DETAIL  
 NOT TO SCALE



4 TYPICAL DETAIL OF PIPE INSTALLATION THROUGH RATED WALL  
 NOT TO SCALE



5 FIRE SPRINKLER RISER DIAGRAM BUILDING/UNIT (TYPICAL FOR EACH)  
 NOT TO SCALE

RELEASED FOR	DATE
<input type="checkbox"/> SCHEMATIC DESIGN	1/26/2024
<input type="checkbox"/> DESIGN DEVELOPMENT	2/21/2024
<input type="checkbox"/> 50% CDS	3/18/2024
<input checked="" type="checkbox"/> PERMIT	3/25/2024

REVISIONS


NO.	DATE	DESCRIPTION




**FIRE PROTECTION GENERAL NOTES:**

1. SPRINKLER SHALL NOT BE LESS THAN 8 FT IN SAME COMPARTMENT
2. PROVIDE SPRINKLER HEADS UNDER FIXED OBSTRUCTIONS OVER 4 FT WIDE. SPRINKLER HEADS SHALL BE COORDINATED WITH FIXED OBSTRUCTIONS AND POSITION HEADS AS PER NFPA FOR ADEQUATE SPRINKLER DISCHARGE PATTERN.
3. NO SPRINKLER HEADS REQUIRED IN BATHROOMS LESS THAN 55 SQFT.
4. PROVIDE CORROSION RESISTANT PROTECTIVE COATING SPRINKLER HEADS IN BATHROOM OVER 55 SQFT.
5. CLOSETS THAT CONTAINS FIRE PROTECTION EQUIPMENT SHALL BE SPRINKLERED REGARDLESS OF SIZE.
6. PROVIDE 20"x20" RESIDENTIAL SPRINKLER IN ALL APARTMENT UNITS.
7. INSTALLING CONTRACTOR TO VERIFY CEILING HEIGHTS/SOFFITS, ANY OPEN TO ABOVE/BELOW SPACES AND MODIFY HEAD LAYOUT IN ACCORDANCE WITH NFPA 13R
8. SPRINKLER HEADS TO MEET MANUFACTURERS MINIMUM PRESSURE AND FLOW REQUIREMENTS (TYPICAL FOR ALL UNITS)
9. ALL HEADS TO BE CENTERED WITH OTHER CEILING DEVICES AND SPACED EQ/EQ
10. FIRE SPRINKLER CONTRACTOR TO COORDINATE WITH INTERIOR DESIGN REFLECTED CEILING PLANS AND MEP CEILING PLANS


IF INSULATION CANNOT BE INSTALLED ON TOP OF SPRINKLER PIPES ON THE THIRD FLOOR, PROVIDE SIDEWALL SPRINKLERS ON 3RD FLOOR UNITS FED FROM THE FLOOR BELOW



**FIRE PROTECTION THIRD FLOOR PLAN - A + B**  
SCALE: 1/4" = 1'-0"



**FIRE PROTECTION SECOND FLOOR PLAN - A + B**  
SCALE: 1/4" = 1'-0"



**FIRE PROTECTION FIRST FLOOR PLAN - A + B**  
SCALE: 1/4" = 1'-0"

FIRE PROTECTION UNIT PLANS	
RELEASED FOR	DATE
<input type="checkbox"/> SCHEMATIC DESIGN	1/26/2024
<input type="checkbox"/> DESIGN DEVELOPMENT	2/21/2024
<input type="checkbox"/> 50% CDS	3/18/2024
<input checked="" type="checkbox"/> PERMIT	3/25/2024


REVISIONS





**FIRE PROTECTION GENERAL NOTES:**

1. SPRINKLER SHALL NOT BE LESS THAN 8 FT IN SAME COMPARTMENT
2. PROVIDE SPRINKLER HEADS UNDER FIXED OBSTRUCTIONS OVER 4 FT WIDE. SPRINKLER HEADS SHALL BE COORDINATED WITH FIXED OBSTRUCTIONS AND POSITION HEADS AS PER NFPA FOR ADEQUATE SPRINKLER DISCHARGE PATTERN.
3. NO SPRINKLER HEADS REQUIRED IN BATHROOMS LESS THAN 55 SQFT.
4. PROVIDE CORROSION RESISTANT PROTECTIVE COATING SPRINKLER HEADS IN BATHROOM OVER 55 SQFT.
5. CLOSETS THAT CONTAINS FIRE PROTECTION EQUIPMENT SHALL BE SPRINKLERED REGARDLESS OF SIZE.
6. PROVIDE 20'X20' RESIDENTIAL SPRINKLER IN ALL APARTMENT UNITS.
7. INSTALLING CONTRACTOR TO VERIFY CEILING HEIGHTS/SOFFITS, ANY OPEN TO ABOVE/BELOW SPACES AND MODIFY HEAD LAYOUT IN ACCORDANCE WITH NFPA 13R
8. SPRINKLER HEADS TO MEET MANUFACTURERS MINIMUM PRESSURE AND FLOW REQUIREMENTS (TYPICAL FOR ALL UNITS)
9. ALL HEADS TO BE CENTERED WITH OTHER CEILING DEVICES AND SPACED EQ/EQ
10. FIRE SPRINKLER CONTRACTOR TO COORDINATE WITH INTERIOR DESIGN REFLECTED CEILING PLANS AND MEP CEILING PLANS


IF INSULATION CANNOT BE INSTALLED ON TOP OF SPRINKLER PIPES ON THE THIRD FLOOR, PROVIDE SIDEWALL SPRINKLERS ON 3RD FLOOR UNITS FED FROM THE FLOOR BELOW



**FIRE PROTECTION THIRD FLOOR PLAN - A + B (MIRRORED)**  
SCALE: 1/4" = 1'-0"



**FIRE PROTECTION SECOND FLOOR PLAN - A + B (MIRRORED)**  
SCALE: 1/4" = 1'-0"



**FIRE PROTECTION FIRST FLOOR PLAN - A + B (MIRRORED)**  
SCALE: 1/4" = 1'-0"

RELEASED FOR	DATE
<input type="checkbox"/> SCHEMATIC DESIGN	1/26/2024
<input type="checkbox"/> DESIGN DEVELOPMENT	2/21/2024
<input type="checkbox"/> 50% CDS	3/18/2024
<input checked="" type="checkbox"/> PERMIT	3/25/2024

REVISIONS


NO.	DESCRIPTION




**FIRE PROTECTION GENERAL NOTES:**

1. SPRINKLER SHALL NOT BE LESS THAN 8 FT IN SAME COMPARTMENT
2. PROVIDE SPRINKLER HEADS UNDER FIXED OBSTRUCTIONS OVER 4 FT WIDE. SPRINKLER HEADS SHALL BE COORDINATED WITH FIXED OBSTRUCTIONS AND POSITION HEADS AS PER NFPA FOR ADEQUATE SPRINKLER DISCHARGE PATTERN.
3. NO SPRINKLER HEADS REQUIRED IN BATHROOMS LESS THAN 55 SQFT.
4. PROVIDE CORROSION RESISTANT PROTECTIVE COATING SPRINKLER HEADS IN BATHROOM OVER 55 SQFT.
5. CLOSETS THAT CONTAINS FIRE PROTECTION EQUIPMENT SHALL BE SPRINKLERED REGARDLESS OF SIZE.
6. PROVIDE 20'X20' RESIDENTIAL SPRINKLER IN ALL APARTMENT UNITS.
7. INSTALLING CONTRACTOR TO VERIFY CEILING HEIGHTS/SOFFITS, ANY OPEN TO ABOVE/BELOW SPACES AND MODIFY HEAD LAYOUT IN ACCORDANCE WITH NFPA 13R
8. SPRINKLER HEADS TO MEET MANUFACTURERS MINIMUM PRESSURE AND FLOW REQUIREMENTS (TYPICAL FOR ALL UNITS)
9. ALL HEADS TO BE CENTERED WITH OTHER CEILING DEVICES AND SPACED EQ/EQ
10. FIRE SPRINKLER CONTRACTOR TO COORDINATE WITH INTERIOR DESIGN REFLECTED CEILING PLANS AND MEP CEILING PLANS


IF INSULATION CANNOT BE INSTALLED ON TOP OF SPRINKLER PIPES ON THE THIRD FLOOR, PROVIDE SIDEWALL SPRINKLERS ON 3RD FLOOR UNITS FED FROM THE FLOOR BELOW



**FIRE PROTECTION THIRD FLOOR PLAN - C + D**  
SCALE: 1/4" = 1'-0"



**FIRE PROTECTION SECOND FLOOR PLAN - C + D**  
SCALE: 1/4" = 1'-0"



**FIRE PROTECTION FIRST FLOOR PLAN - C + D**  
SCALE: 1/4" = 1'-0"

RELEASED FOR	DATE
<input type="checkbox"/> SCHEMATIC DESIGN	1/26/2024
<input type="checkbox"/> DESIGN DEVELOPMENT	2/21/2024
<input type="checkbox"/> 50% CDS	3/18/2024
<input checked="" type="checkbox"/> PERMIT	3/25/2024


REVISIONS





**FIRE PROTECTION GENERAL NOTES:**

1. SPRINKLER SHALL NOT BE LESS THAN 8 FT IN SAME COMPARTMENT
2. PROVIDE SPRINKLER HEADS UNDER FIXED OBSTRUCTIONS OVER 4 FT WIDE. SPRINKLER HEADS SHALL BE COORDINATED WITH FIXED OBSTRUCTIONS AND POSITION HEADS AS PER NFPA FOR ADEQUATE SPRINKLER DISCHARGE PATTERN.
3. NO SPRINKLER HEADS REQUIRED IN BATHROOMS LESS THAN 55 SQFT.
4. PROVIDE CORROSION RESISTANT PROTECTIVE COATING SPRINKLER HEADS IN BATHROOM OVER 55 SQFT.
5. CLOSETS THAT CONTAINS FIRE PROTECTION EQUIPMENT SHALL BE SPRINKLERED REGARDLESS OF SIZE.
6. PROVIDE 20'X20' RESIDENTIAL SPRINKLER IN ALL APARTMENT UNITS.
7. INSTALLING CONTRACTOR TO VERIFY CEILING HEIGHTS/SOFFITS, ANY OPEN TO ABOVE/BELOW SPACES AND MODIFY HEAD LAYOUT IN ACCORDANCE WITH NFPA 13R
8. SPRINKLER HEADS TO MEET MANUFACTURERS MINIMUM PRESSURE AND FLOW REQUIREMENTS (TYPICAL FOR ALL UNITS)
9. ALL HEADS TO BE CENTERED WITH OTHER CEILING DEVICES AND SPACED EQ/EQ
10. FIRE SPRINKLER CONTRACTOR TO COORDINATE WITH INTERIOR DESIGN REFLECTED CEILING PLANS AND MEP CEILING PLANS


IF INSULATION CANNOT BE INSTALLED ON TOP OF SPRINKLER PIPES ON THE THIRD FLOOR, PROVIDE SIDEWALL SPRINKLERS ON 3RD FLOOR UNITS FED FROM THE FLOOR BELOW



**FIRE PROTECTION THIRD FLOOR PLAN - C + D  
(MIRRORED)**  
SCALE: 1/4" = 1'-0"



**FIRE PROTECTION SECOND FLOOR PLAN - C + D  
(MIRRORED)**  
SCALE: 1/4" = 1'-0"



**FIRE PROTECTION FIRST FLOOR PLAN - C + D  
(MIRRORED)**  
SCALE: 1/4" = 1'-0"

FIRE PROTECTION UNIT PLANS	
RELEASED FOR	DATE
<input type="checkbox"/> SCHEMATIC DESIGN	1/26/2024
<input type="checkbox"/> DESIGN DEVELOPMENT	2/21/2024
<input type="checkbox"/> 50% CDS	3/18/2024
<input checked="" type="checkbox"/> PERMIT	3/25/2024

REVISIONS
